

***MTPi2000C - 80 KW (RANGE)*****TECHNICAL DESCRIPTION****1 GENERAL DESCRIPTION**

The MTPi2000C - 80 kW system is designed to convert AC mains voltage into 48 VDC and to supply telecom equipments with back up batteries.

The MTPi2000C - 80 kW can house up to forty SMi2000HD rectifier modules and can be used with 48 V valve regulated lead-acid (VRLA) batteries strings.

The maximum total power that can be used is 80 kW.

The MTPi2000C - 80 kW is fitted with:

- Mains 3Ph+N connection,
- Wiring and space for up to forty SMi2000HD rectifiers,
- One ACMi1000HD alarm and control module,
- A battery low voltage disconnect contactor (LVD : 1500 A rated),
- Battery shunt,
- Battery protections: two fuses NH4 (up to 1250 A), or four fuses NH4 (up to 1250 A), or configured to customer requirements,
- Load protections: Configured to customer requirements.



Example of configuration: MTPi2000C - 80 kW in 600 x 600 x 2000 cabinet (On the right: front view without the door)

***MTPi2000C - 80 kW* TECHNICAL DESCRIPTION**

## 2 STANDARD OPTIONS

The following standard options are available:

- **Mains:**
  - Flexible mains grid connection 3 Ph+N / 3 Ph.
  - Mains input MCB / Mains switch.
  - Surge Protective Device (SPD).
  - Over Voltage Protection - Loss of neutral protection module (OVP).
  
- **Protection devices:**
  - Battery protections (fuses; Standard qty = 2; maximum is 4).
  - Load distribution protections (fuses or circuit breakers, with or without trip monitoring).
  - Non Priority Load Disconnect (NPLD).
  - Magnetically latched contactors (LVD/PLD).
  
- **Mechanicals:**
  - Door (anti clockwise).
  - Extension distribution cabinet (coupled).
  - Seismic cabinet.
  - Lifting bolts.
  
- **Communication:**
  - Ethernet / TCP-IP.
  - Modem (PSTN, GSM).
  - RS485.
  
- **Miscellaneous:**
  - T° probe > 10 m (up to 30 m).
  - Emergency shutdown.
  - AC Inverter.

## 3 OTHER OPTIONS

Specific requirements may be installed (subject to application engineering).

## 4 STANDARDS

- **Safety:**
  - EN 60950-1, UL/CSA 60950-1
  
- **EMC:**
  - Emission:
    - EN 55022 level B
    - . complies with EN 61000.6-3 (generic residential)
    - . complies with EN 61000.6-4 (generic industrial)
    - . complies with EN 61000.3-2 (harmonics)
    - . complies with EN 61000.3-3 (flicker)
  - Immunity:
    - . complies with EN 61000.6-1 (generic residential)
    - . complies with EN 61000.6-2 (generic industrial)
    - . standards from EN 61000.4-2 to EN 61000.4-6
    - . 'ANSI' surge C62.41
  - Telecom standard
    - . EN 300 386 – 2
  
- **Environmental conditions:**
  - . Complies with EN 300 019
  - . Transport EN 300 019-1-2 class 2.2
  - . Storage EN 300 019-1-1 class 1.2
  - . Operation EN 300 019-1-3 class 3.1
  
- **Operating conditions:**
  - . Complies with EN 300 132-2 (Telecom standard).

## 5 CHARACTERISTICS

### 5.1 ENVIRONMENTAL CHARACTERISTICS

- **Temperature**
  - Shipping and storage : -40 °C to +85 °C.
  - Operating : -25 °C to +45 °C.
  
- **Humidity**
  - Shipping and storage : 5 to 95% relative humidity non-condensing.
  - Operating humidity : 5 to 95% relative humidity non-condensing.
  
- **Altitude**
  - Operating : 0 - 2500 m without power derating.
  
- **Cooling**
  - Forced air cooling with electronic speed control.

## 5.2 MECHANICAL CHARACTERISTICS

- Height : 2000 mm.
- Width : 600 mm.
- Depth : 600 mm.
- Weight : 200 kg (subject to options fitted).
- Degree of protection : IP 20.
- Access : Front.
- Cable entry : Top.

## 5.3 ELECTRICAL CHARACTERISTICS

<b><i>MTPi2000C-80kW SYSTEM</i></b>	
Rectifier maximum output power	80 kW (1668 A @ 48 V)
Load / Battery maximum output power	64.8 kW (1500 A @ 43.2 V)
<b><i>DIELECTRIC STRENGTH</i></b>	
AC line to output	4200 VDC (3000 Vrms)
AC line to chassis	2100 VDC (1500 Vrms)
Output to chassis	700 VDC (500 Vrms)
<b><i>INPUT</i></b>	
Nominal voltage	Three-phase + neutral mains: 380 Vrms / 400 Vrms / 415 Vrms
Normal variations	180 V to 264 Vrms Phase / neutral.
Exceptional variations	90 V to 300 Vrms Phase / neutral with: <ul style="list-style-type: none"> <li>. power de-rating below 180 Vrms</li> <li>. automatic disconnect on low (&lt; 90 V) and high (&gt; 300 V) voltage out of range with automatic re-start.</li> </ul>
Frequency	45 to 66 Hz
Nominal current	9.5 A per rectifier for 2000 W at 230 Vrms
Inrush current	< 40 A (for only one rectifier)
Power factor	0.98 typical
<b><i>OUTPUT</i></b>	
Nominal voltage	48 VDC Remotely by CAN loop. Adjustment range: 42 V to 57 V.
Floating voltage	Adjustable between 48 VDC and 57 VDC
Maximum power	2000 W up to 75 °C ambient temperature, per rectifier module (automatic de-rating above 55 °C)
Current sharing	< ± 5% at P > Pn/2
<b><i>RECTIFIER EFFICIENCY</i></b>	
92%	

## 6 INDICATORS AND ALARMS

### 6.1 INDICATORS ON ACMi1000HD AND SMi2000HD

Refer to the corresponding data sheets.

### 6.2 ALARM LOOPS

The following alarms, delivered by the ACMi1000HD, are available across volts-free contacts on screw terminal connector:

- Mains off
- Urgent alarm
- Non-urgent alarm
- Spare: 3 alarm loops (configured to customer requirements).

## 7 PACKAGING AND PRODUCT REFERENCE

### 7.1 PACKAGING

Carton case, filmed, on pallet.

### 7.2 PACKING TABLE

<i>MTPi2000C-80KW cabinet</i> packed dimensions and weight		
W x D x H	mm	720 x 720 x 2200
Gross Weight	kg	210 kg (subject to options fitted)
Volume	m <sup>3</sup>	1.14

### 7.3 PRODUCT REFERENCE

Designation	AEG's Code
MTPi2000C - 80 kW	Customer specific

## 8 ASSOCIATED PRODUCTS

Designation	AEG's Code
SMi2000HD rectifier module	3AW01177ACAA
Supervision:	
ACMi1000HD controller (controller & display)	3AW17197ABAA
ACMi1000HD-1U with TCP-IP (complete 1U rack)	B05370841000
ACMi1000HD-1U without TCP-IP (complete 1U rack)	3TN00003AAAA
WINi1000 supervision software	B00821920000

## 9 SUPPLIER

**AEG Power Solutions**

10, rue Jean Perrin BP359  
37173 Chambray Les Tours Cedex  
FRANCE

Phone : 33 (0) 247 808 860

Fax : 33 (0) 247 280 719

Internet : [www.aegps.com](http://www.aegps.com)

AEG Power Solutions offers installation, customization and technical support services.  
Contact your local re-seller.